



NEW VISOR WITH Highbrow POSITION LIGHTS



NEW TAIL LAMPS WITH LED LIGHT GUIDES



WIDER REAR TYRE



DUAL FINISH SPORTY MUFFLER



INTEGRATED DIGITAL CONSOLE & ENGINE IMMOBILIZER



UNDER SEAT MOBILE CHARGER SOCKET

ENGINE		Brakes Front	Disc (240 mm)
Type	Air cooled, 4 - stroke single cylinder OHC	Brakes Rear	Internal expanding shoe type (130 mm) Optional - Disc (220 mm)
Bore x Stroke	57.3 x 57.8 mm	ELECTRICALS	
Displacement	149.2 cc	Battery	12 V - 4 Ah, MF Battery
Maximum Power	10.6 KW (14.4 Ps) @ 8500 rpm	Head Lamp	12 V - 35 W / 35 W - Halogen Bulb - Trapezoidal Multi Reflector Type
Maximum Torque	12.80 N m @ 6500 rpm	Tail / Stop Lamp	12 V - 0.5 W / 4.1 W (LED lamps)
Ignition	AMI - Advanced Microprocessor Ignition System	Turn Signal Lamp	10 W x 4nos. [Amber Bulb, Clear Lens Multi Reflector Type]
Starting	Self Start / Kick Start	DIMENSIONS	
Carburetor	CV type with Carburetor Controlled Variable Ignition	Length	2060 mm
TRANSMISSION		Width	765 mm
Clutch	Multiplate wet	Height	1145 mm
Gear box	5 Speed constant mesh	Wheelbase	1325 mm
CHASSIS		Ground Clearance	145 mm
Type	Tubular, Diamond Type	WEIGHTS	
SUSPENSION		Kerb Weight	145 kg (Rear Brakes - Drum) 146 kg (Rear Brakes - Disc)
Front	Telescopic Hydraulic Type	Fuel tank capacity	12.1 litre (Min)
Rear	Rectangular Swing Arm with 5 step Adjustable Gas Reservoir Suspension	Reserve	1.5 litre (Usable reserve)
WHEEL & TYRES			
Rim Size Front	18 x 1.85, Alloy Wheels		
Rim Size Rear	18 x 2.15, Alloy Wheels		
Tyre Size Front	80 / 100 x 18 - 47 P		
Tyre Size Rear	110 / 90 x 18 - 61 P		

Accessories and features shown may not be a part of the standard fitment. It is our endeavour to constantly improve our products. This could lead to changes in product specifications without notice. Hero Xtreme complies with BS III norms.



ORANGE



BLUE



BLACK



SILVER



RED

